

## ADDENDUM 001

ITB 18-ACI-003

09/24/2018

This document is made a part of the original bid documents and replaces or adds to the bid as instructed below.

The following is added to the itemized specifications delineating some of the standard features:

The forklift is to be equipped with a 3-way muffler system which conforms to current Federal EPA regulations for off-road large spark ignited engines.

The forklift is to be equipped with active control rear stabilizer, Active Mast Function Controller, Automatic fork Leveling, 4 way adjustable full suspension seat,

Mast: 3-stage (FSV) mast with full free lift. Max fork height -189", overall lowered height-83.3". Free lift-35.3" with standard load backrest.

Base model capacity-5,000lbs @ 24" load center. Actual capacity 4,500 lbs@24" load center to 189" MFH. Ratings based on standard unit with standard features.

Tilt: 6 degrees forward, 5 degrees backwards.

Carriage: ITA Hook Type, 36" Carriage

Forks: 42" x 5" x 1.6" class II

Attachments: Cascade 36" hang-on side shifter (includes 3<sup>rd</sup> function internal hosing)

Speeds: Travel 10.6 mph. Lift 121 fpm

Engine: 2.2L 136 cid 4 cylinder OHV.

Automatic Transmission 1 speed forward 1 speed reverse.

Steering: Load Sensing Hydrostatic Power Steering w/Tilt column

Tires: Front 21x7x15. Rear 16x5x10.5

Lighting: Adjustable headlights with guards. Automotive style switch.

END OF ADDENDUM